

FABRIC

Verona™ NP is a medium weight, all purpose, woven, polyester-based, commercial grade fabric that offers best-in-class performance and features.

FEATURES & BENEFITS

- Commonly used alternative to exposed double wall duct
- Guaranteed not to condensate
- Limited air is able to pass through the fabric weave
- Desired airflow can be delivered exclusively through the porous fabric or combined with various venting options
- Machine washable


FABRIC SPECIFICATIONS

Weave: Fire Retardant Polyester | Filament Spun Plain
 Weight: 6.5 oz/yd² (220g/m²)
 Porosity: 0.7 CFM/ft² @ 0.5in w.g (3.6 L/s/m² @ 125Pa)
 Codes: Classified by Underwriters Laboratories in accordance with the requirements of:

- NFPA 90A • UL 2518 • UL-C (Canada)
- AS/NZS 1530.3-1999 (Australia / New Zealand)



SHAPE



COLOR



SUSPENSION

WARRANTY	SkeleCore FTS	SkeleCore Pull-Tight	IHS (Hoops)	Hangers	1, 2 or 3 Row	Surface Mount
	✓	✓	✓	✓	✓	✓
	15 yrs Pro-rated 11-15yrs	10 yrs			10 yrs Pro-rated 8-10yrs	

See full warranty sheet for application and airflow requirements

AIR DISPERSION

Air Porous	Linear Vents	Orifices	Grommets	Adjustable Nozzles	Fixed Nozzles
✓	✓	✓	✓	✓	✓